



Z型
单侧带防尘盖



ZZ型
双侧带防尘盖



Z型
单侧带防尘盖




ZZ型
双侧带防尘盖

ITEM NO.	d mm	D mm	B mm	Basic rated load (KN)		Maxrunco
				Dynamic	Static	Grease
				Cr	Cor	r/min
6000	10	26	8	4.55	1.96	20000
6001	12	28	8	5.1	2.39	19000
6002	15	32	9	5.6	2.84	18000
6003	17	35	10	6.8	3.35	17000
6004	20	42	12	9.4	5.05	15000
6005	25	47	12	10.1	5.85	13000
6006	30	55	13	13.2	8.3	12000
6007	35	62	14	16	10.3	10000
6008	40	68	15	16.8	11.5	8000
6009	45	75	16	21	15.1	7200
6010	50	80	16	21.8	16.6	6400
6011	55	90	18	28.3	21.2	5700
6012	60	95	18	29.5	23.2	5000
6013	65	100	18	31.9	25	4800
6014	70	110	20	39.7	31	4600
6015	75	115	20	41.6	33.5	4400
6016	80	125	22	47.5	40	4300
6017	85	130	22	49.5	43	4200
6018	90	140	24	58	49.5	4000
6200	10	30	9	5.1	2.39	19000
6201	12	32	10	6.1	2.75	18000
6202	15	35	11	7.75	3.6	17000
6203	17	40	12	9.6	4.6	16000
6204	20	47	14	12.8	6.65	14000
6205	25	52	15	14	7.85	12000
6206	30	62	16	19.5	11.3	10000
6207	35	72	17	25.7	15.3	8800
6208	40	80	18	29.1	17.8	7700
6209	45	85	19	32.5	20.4	6800
6210	50	90	20	35	23.2	6100
6211	55	100	21	43.5	29.2	5500
6212	60	110	22	52.5	36	5000
6213	65	120	23	58.5	40.5	4800
6214	70	125	24	63.7	45	4600
6215	75	130	25	68.9	49	4400
6216	80	140	26	72.5	53	4200
6300	10	35	11	8.2	3.5	15000
6301	12	37	12	9.7	4.2	14000

6302	15	42	13	11.4	5.45	13000
6303	17	47	14	13.5	6.55	12000
6304	20	52	15	15.9	7.9	11000
6305	25	62	17	21.2	10.9	10000
6306	30	72	19	26.7	15	8000
6307	35	80	21	33.5	19.1	6800
6308	40	90	23	40.5	24	5800
6309	45	100	25	53	32	5000
6310	50	110	27	62	38.5	4400
6311	55	120	29	74.1	45	4200
6312	60	130	31	85.2	52	4000
6313	65	140	33	97.5	60	3900
6314	70	150	35	111	68	3800
6315	75	160	37	119	76.5	3600
6403	17	62	17	22.7	10.8	14000
6404	20	72	19	28.5	13.9	12000
6405	25	80	21	34.5	17.5	10000
6406	30	90	23	43.5	23.9	8800
6407	35	100	25	55	31	7800
6408	40	110	27	63.5	36.5	7000
6409	45	120	29	77	45	6300
6410	50	130	31	83	49.5	5700
6411	55	140	33	89	54	5200
6412	60	150	35	102	64.5	4800
6413	65	160	37	111	72.5	4400
6414	70	180	42	128	89.5	4100
6415	75	190	45	138	99	3800
6416	80	200	48	164	125	3600
6417	85	210	52	165	128	3400
6418	90	225	54	184	149	3200
6419	95	240	55	186	153	3000
6420	100	250	58	206	175	2900

ITEM NO.	d	D	B	Basic rated load (N)		Allow
				Dynamic	Static	revol
				Cr	Cor	Grease
	mm	mm	mm			*100
6700ZZS	10	15	4	855	435	15
6800ZZ		19	5	1716	840	37
63800ZZ		19	7	1716	840	37
6900ZZ		22	6	2695	1273	34
6701ZZS	12	18	4	926	530	13
6801ZZ		21	5	1915	1041	33
63801ZZ		21	7	1915	1041	33
6901ZZ		24	6	2886	1466	31
6702ZZS	15	21	4	937	582	11
6802ZZ		24	5	2073	1253	28
63802ZZ		24	7	2073	1253	28
6902ZZ		28	7	4321	2259	26
6703ZZS	17	23	4	1000	658	9.5
6803ZZ		26	5	2233	1456	26
63803ZZ		26	7	2233	1456	26
6903ZZ		30	7	4588	2565	23

6704ZZS	20	27	4	1402	729	8.5
6804ZZ		32	7	4015	2462	21
63804ZZ		32	10	4015	2462	21
6904ZZ		37	9	6381	3682	19
6705ZZ	25	32	4	1091	838	7
6805ZZ		37	7	4303	2932	18
63805ZZ		37	10	4303	2932	18
6905ZZ		42	9	7001	4540	16
6706ZZ	30	37	4	1143	947	5.5
6806ZZ		42	7	4538	3402	15
63806ZZ		42	10	4538	3402	15
6906ZZ		47	9	7242	5003	14
6707ZZ	35	44	5	1866	1635	4.9
6807ZZ		47	7	4729	3821	13
6907ZZ		55	10	10900	7818	12
6708ZZ	40	50	6	2516	2233	4.3
6808ZZ		52	7	4923	4178	12
6908ZZ		62	12	13678	9968	11
6709ZZ	45	55	6	2580	2397	3.9
6809ZZ		58	7	6187	5381	11
6909ZZ		68	12	14100	10830	9.7
6710ZZ	50	62	6	2670	2640	3.5
6810ZZ		65	7	6610	6090	9.6
6910ZZ		72	12	14540	11710	9
6811ZZ	55	72	9	8800	8100	8.7
6911ZZ		80	13	16600	14100	8.1
6812ZZ	60	78	10	11500	10600	8
6912ZZ		85	13	20200	17300	7.5
6813ZZ	65	85	10	11900	11500	7.3
6913ZZ		90	13	17400	16100	7.1
6814ZZ	70	90	10	12100	11900	6.8
6914ZZ		100	16	23700	21200	6.4
6815ZZ	75	95	10	12500	12900	12.5
6915ZZ		105	16	24400	22600	6.1
6816ZZ	80	100	10	12700	13300	12.7
6916ZZ		110	16	25000	24000	5.7
6817ZZ	85	110	13	18700	19000	5.6
6917ZZ		120	18	31900	29600	5.3
6818ZZ	90	115	13	19000	19700	5.3
6918ZZ		125	18	32800	31600	5.1



out speed	Weight
Oil	
r/min	Kg/pc
28000	0.019
26000	0.021
24000	0.03
22000	0.039
19000	0.069
17000	0.08
15000	0.116
13000	0.155
11000	0.185
9000	0.231
7800	0.25
7000	0.362
6300	0.385
6100	0.44
5800	0.6
5600	0.64
5500	0.854
5300	0.89
5100	1.02
26000	0.032
24000	0.037
22000	0.045
20000	0.066
18000	0.106
16000	0.128
13000	0.199
10000	0.287
9200	0.367
8200	0.416
7300	0.462
6600	0.602
6000	0.789
5800	0.99
5600	1.1
5400	1.2
5300	1.4
21000	0.053
20000	0.06

18000	0.082
17000	0.115
15000	0.144
13000	0.2193
10000	0.3498
8000	0.4542
7200	0.6394
6200	0.8363
5500	1.0822
5300	1.35
5100	1.7
5000	2.1
4800	2.5
5600	3

16000	0.27
14000	0.4
12000	0.53
10000	0.735
9100	0.952
8200	1.23
7400	1.53
6700	1.88
6100	2.29
5700	2.77
5200	3.3
4800	4.83
4500	5.72
4200	6.76
4000	7.95
3800	11.4
3500	13.4
3400	15

Variable Rotation	Weight
Oil	(g)
0rpm	
17	1.9
43	5.6
43	7.4
41	10
15	3.1
39	6.5
39	8.5
36	12
13	3.6
33	7.6
33	10
30	19
11	4
30	8.2
30	11
38	20

10	5.9
25	18
25	24
23	40
8	7.1
21	24
21	32
19	47
7	8.3
18	27
18	36
17	53
6	15
16	32
14	87
5	23
14	35
13	131
4.6	25
13	42
11	147
4.1	64
11	52
11	133
10	83
9.6	185
9.4	104
8.9	192
8.6	126
8.4	211
8.1	134
7.6	342
12.9	142
7.2	363
13.3	150
6.8	382
6.6	266
6.3	535
6.3	279
6	565